







TRIMS



Sidewall S4



Solid Z Closure Z4



Chalet Gable CG1



Offset Cleat 01

STANDARD WIDTHS

14" | 18"

FINISHES

22 ga | 24 ga | 26 ga | 28 ga | 26 ga TEX | Aluminum .032 | .040

PROFILE OPTIONS

Single lock panel Double lock panel

Radius panel (single or double lock)


PRODUCTION OPTIONS

Factory made or field rolled to exact lengths. Optional: striation, flat panel, clip relief

INSTALLATION


Can be installed over steel decking with Polyiso, or plywood decking with high temp ice & water shield.

Recommended minimum slope 1/2:12




3/8"


End Wall E1



Drip Edge D1



Drip Edge D2



Drip Edge D3








Hip H3 | Ridge R3








Valley V1





Counter Flashing CF1 Counter Flashing CF2



Panels have demonstrated compliance with UL580, Class 90.

Product Description: Ultra-Clad pre-finished metal features Dura Coat Durapon 70% full strength PVDF paint finishes formulated with Cool technology. This high performance product provides the ultimate in resistance against fading and weathering. In addition to our standard colors, custom colors are also available up request.

Color Samples: Colors shown represent the actual colors as accurate as modern printing technology will permit. Colors represented on electronic charts may not match actual material. All colors should be verified using actual metal samples. Mismatch of electronic color representation and actual material shall not be accepted as a cause for rejection. Free metal samples are available upon request.

